

JVLT Combo Trailer



General Specifications:

- 500 gallon debris capacity
- 325 gallon water capacity
- Stainless steel water tanks
- 2 ½" water fill hook-up
- 95 hp water cooled diesel engine
- High temperature/low oil shutdown on engine for safety and longevity
- Simple controls located on the swing arm of the trailer
- 800CFM positive displacement blower
- Vacuum capability of 16" Hg
- 180° hydraulic reel articulation
- 360° hydraulic boom rotation with pendant control
- Hydraulic door locks
- Centrifugal strainer with perforated stainless steel insert
- Water pump capable of 18 GPM @ 3500 psi
- 400' of ½" jetting hose
- Low water level shutdown
- Easy winterization hook-up to protect water pump and hoses
- Gear driven hydraulic pump mounted on engine
- Water pump and vacuum blower capable of being operated independently or simultaneously
- 45° dump angle on debris tank
- Top-opening rear door for safe and easy access or cleaning
- Easy opening rear door with dual sight-level gauges
- 6" gate valve on rear door
- Rugged 12,000 GVW trailer built to heavy-duty construction specifications
- Balanced trailer layout to maintain even weight distribution
- Tool/accessory holders
- Approx. overall length – 22'
- Approx. overall width – 96"
- Four - 4" x 6' extension tubes, cam lock style
- One - 4" x 6' intake tube, cam lock style

Available Options:

- Hydro-excavating package
- Remote control
- Hydraulic tool kit
- Internal tank flush out system
- IntelACount