BUTTON NOSE NOZZLES









BUTTON NOSE FLUSHERS

Good general purpose cleaning nozzle. Also for follow up after cleaning out blockages to remove left over debris. For runs up to 100 ft. Button nose nozzles are made of heat treated 416 Stainless Steel.

Part No.	Prop Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
140215FL	45°	6	0	1.7	1500	1/4"
380430BNFL	45°	6	0	4	3000	3/8"
380530FL	45°	6	0	4.8	3000	3/8"




NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.


BUTTON NOSE PENETRATORS

Button Nose nozzles with a forward jet to bore through plugged lines. Made of heat treated 416 Stainless Steel.

						STATE STREET, STATE OF THE STATE OF
Part No.	Prop Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
180215PE	25°	3	1	1.7	1500	1/8"
180430PE	25°	3	1	4	3000	1/8"
140215PE	25°	3	1	1.7	1500	1/4"
380430BNPE	25º	4	1	4	3000	3/8"
380530PE	250	3	1	4.8	3000	3/8"



NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.



Button Nose nozzles can be custom drilled to meet your specifications. The dual groove design permits a wide range of spray angles that can be utilized. The rear groove allows for high thrust angles from 25° to 35°. The forward groove accommodates flushing angles from 45° to 70°. The nose area permits angles of 0° (straight forward) to 45°. Made of heat treated 416 Stainless Steel. See caution note below.



A word of caution on custom drilled nozzles: Make sure all the information is correct when ordering as these nozzles will be drilled to order and are not returnable.






RADIAL NOZZLES

ROUND HEAD SUPER THRUSTERS

Good general purpose cleaning nozzle. Also for follow up after cleaning out blockages to remove left over debris. For runs up to 100 ft. Button nose nozzles are made of heat treated 416 Stainless Steel.



Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
180430PE	15°	3	1	4	3000	1/8"
380530RHTH	15°	3	1	4.8	3000	3/8"



Round Head Super Thruster nozzles can be custom drilled to meet your specifications. The 15° to 20° angle range allows for maximum pulling power with one forward jet to penetrate blockages. Pattern: 3 to 6 rear jets with 1 forward jet. Made of heat treated 416 SS. See caution note on page 1.



Custom drilled O'Brien style Radial Nose (RN) nozzles are available to meet your specifications. They are designed to accommodate a range of spray angles from 18° for high thrusting power up to 65° for flushing action. Side wall jets of 90° are possible, as well as forward jets from 0° to 45°. 6 to 12 rear jets, 0 to 3 forward. Made of heat treated 416 Stainless Steel. See caution note on page 1.

		A THE SECTION AS A		The same of the same	The state of the s	2.00
Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A136015	15º	6	0	35	2000	3/4"
344020RNTH	15º	6	0	40	2000	3/4"
A136001	15º	6	0	60	2000	1"
A136000	15°	6	0	65	2000	1"
A136423	15°	6	0	65	2500	1"
A136002	15°	6	0	80	2000	1"
A136023	15°	6	0	80	2500	1"
A136007-1	15°	6	0	100	2000	1"
A136063	15°	6	0	80	2000	1-1/4"
A136003	15°	6	0	100	2000	1-1/4"
A100190	15º	6	0	125	2000	1-1/4"



NOTE: Only common configurations for our units are listed above.

Call us if you require a different configuration.





PENETRATING RADIAL THRUST NOZZLES

Radial Nozzles with a forward jet to break up blockages ahead of the nozzle.

10000000000000000000000000000000000000	Security adaptive stock to the	PAROMED VIANTED			V. PSP OF REAL MODES	
Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
121025PE	25º	6	1	10	2500	1/2"
121230PE	25º	6	1	12	3000	1/2"
121840PE	25º	6	1	18	4000	1/2"
123030PE	25º	6	1	30	3000	1/2"
341840PE	25º	6	1	18	4000	3/4"
343030PE	25°	6	1	30	3000	3/4"
344020RNTH	18º	6	1	40	2000	3/4"
344020PE	25º	6	1	40	2000	3/4"
344520PE	18º	6	1	45	2000	3/4"
J-1147	18º	6	1	65	2000	1"
018020PE	25º	6	1	80	2000	1"
A136023-F	15°	6	1	80	2500	1"

RADIAL FLUSHER NOZZLES

Designed for general cleaning applications in small and medium sized pipes.

				The second second		
Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
121025FL	35º	6	0	10	2500	1/2"
121536FL	35º	6	0	15	3600	1/2"
121840FL	35°	6	0	18	4000	1/2"
123030FL	35º	6	0	30	3000	1/2"
343030FL	35º	6	0	30	3000	3/4"
A136020	35º	6	0	35	2000	3/4"
344020FL	35º	6	0	40	2000	3/4"
A136052	35º	6	0	45	2000	3/4"
J-1015 (Mushroom)	30º	6	0	65	2000	1"
A136005	35º	6	0	65	2000	1"
A136424	35°	6	0	65	2500	1"
A136007	35º	6	0	80	2000	1"
A136024	35º	6	0	80	2500	1"
A136008	35°	6	0	100	2000	1-1/4"
A100191	35º	6	0	125	2000	1-1/4"

NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.







PENETRATING RADIAL FLUSHER NOZZLES

Radial Nozzles with a forward jet to break up blockages ahead of the nozzle.

Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A136385	300	5	1	20/25	2500/4000	1/2"
343520PE	300	6	1	35	2000	3/4"
344029RNFL	30°	6	1	40	2000	3/4"
J-1021	300	6	1	65	2000	1"
J-1141	30°	6	1	65	2000	1"

NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.

RADIAL VORTEX (AKA MONSTER) NOZZLES

Vortex dual degree design incorporates powerful thrust and wide angle cleaning into one nozzle. For general cleaning applications in small and medium sized pipes.

	Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
	121840RNMO	25º/45º	8	0	18	4000	1/2"
	A136025	15º/35º	6	0	40	2000	3/4"
	344020RNMO	25º/45º	8	0	40	2000	3/4"
100000	A136010	15º/35º	6	0	65	2000	1"
	A136011	15º/35º	6	0	80	2000	1"

NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.

PENENTRATING RADIAL VORTEX NOZZLE

Vortex dual degree design incorporates powerful thrust and wide angle cleaning into one nozzle. For general cleaning applications in small and medium sized pipes.

Market With Santa	PERSON DEBUSEMENT OF LE	The Control of the Co		The Late Charles of the Late Charles		
Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
121025RNMV	18º/25º	6	1	10	2500	1/2"
J-1132	18º/24º	6	1	35	2000	3/4"
016520RNMV	18º/25º	6	1	65	2000	1"

NOTE: Only common configurations for our units are listed above. Call us if you require a different configuration.





RADIAL DEGREASER/DEICER NOZZLE

Same purpose as the Penetrating Radial Vortex Nozzle, but for larger hoses.

See information on page 4 for custom drilled radial nozzles.


Pa	art No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
344	1020DE	35°	6	3 @ 10º	40	2000	3/4"
016	520DE	35º	6	3 @ 100	65	2000	1"



JUMPER DEGREASER/DEICER NOZZLES

Designed to penetrate heavy grease, soap, and ice filled lines. A great all-around nozzle! New style made of heat treated 416 stainless steel. Note: Old style degreaser/deicer nozzles are being phased out as existing inventories are depleted.

	Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
9	380530DE	45°	6	3 @ 100	4	3000	3/8"
	121025DE	45°	6	3 @ 100	10	2500	1/2"
Ų.	121536DE	45°	6	3 @ 100	15	3600	1/2"
	121840DE	45°	6	3 @ 10º	18	4000	1/2"



Custom drilled Degreaser/Deicer nozzles are available to meet your machines specifications. Made of heat treated 416 stainless steel, they all feature three 10° forward jets and 6 to 8 rear jets at a choice of 35° or 45° angles. If higher thrust is desired, order a 25° button nose nozzle with three 10° forward jets (see Button Nose nozzles). See caution note on page 1.

GREASE REMOVER NOZZLES

More rear jets for removing grease and detergent from the pipe wall.



Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A130197	350	10	0	25	4000	1/2"
A130196	350	12	0	25	4000	3/4"
A130195	350	12	0	65	2000	1"
A130198	350	12	0	80	2000	1"





TRIAD PENETRATOR

Triangular shape allows for excellent penetration. Features three front faces with 15° orifices and a penetrating front tip orifice. Made of stainless steel. Used for cleaning calcium, dirt, grease and soap build up. Also very effective for ice penetration. Orifices are replaceable. Imported.

Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A135990	25°	6	4	5	4000	1/4"
A135994	25°	6	4	12	2000	1/2"
A135991	25°	6	4	20	2000	1/2"
A135992	25°	6	4	35	2000	3/4"
A135996	25°	6	4	40	2000	3/4"
A135993	25°	6	4	65	2000	1"
A135995	25º	6	4	80	2000	1"



ELLIPSE NOZZLES

This is the best long lasting nozzle made. Wear-Resistant high carbon steel construction. This smooth surface nozzle will penetrate through blockages and is capable of being retrieved without binding on offset joints, broken pipes or tight bends. Orifices are replaceable.

Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A136160	15°	6	1	20	2000	1/2"
A136155	15°	6	1	35	2000	3/4"
A136150	15°	6	1	65	2000	1"
A136165	15°	6	1	65	2000	1"
A136151	15°	6	1	80	2000	1"



PENETRATOR NOZZLES

The Penerating Nozzle breaks up stoppages to clear plugged lines.

Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
J-1102	30°	5	0	40	2000	3/4"
J-1104-80	30°	5	0	80	2000	1"







SPEAR POINT NOZZLES

Great for penetrating through and breaking up blockages in 6" to 12" pipe.



	Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
100	J-1134	12º	6	1	35	2000	3/4"
Г	J-1139	16º	6	1 (4 side)	35	2000	3/4"

RADIAL WITH LANCE TIP NOZZLES

For cleaning totally blocked lines. 90° spray from lance tip opens a hole in blockage allowing the nozzle to jump forward.



	Part No.	Prop. Angle	Rear Jets	Lance Jets	GPM	PSI	NPT Size
ſ	A136018	15°	6	6	65	2000	1"

ASSEMBLE YOURSELF 11º THRUST NOZZLE

Lightweight, fast, forward traveling nozzle. The 11° rearward-facing jet stream is ideal for use in deteriorating concrete pipe. A 1/4" pipe fort in front can be equipped with lance, front orifice or just plugged. Order all indicated parts in the appropriate column.

Part No.	Description	3/4" 40@2000	1" 65@2000	1" 80@2000
A131420	1" NPT Blank Cast Aluminum Body	1	1	1
A133740	1" to 3/4" Pipe Reducer	1		
A131541	1/8" NPT #10 Rear Orifice	6		
	1/8" NPT #15 Rear Orifice		6	3
A131544	1/8" NPT #30 Rear Orifice			3
A133365	1/4" NPT Front Plug	1	1	1
A131561	1/8" NPT Lance Tip	Optional	Optional	Optional
A131655	1/4" MNPT X 1/8" FNPT Lance Tip Ext.	Optional	Optional	Optional
A131520	1/4" NPT #6 Front Orifice	Optional	Optional	Optional







ASSEMBLE YOURSELF AQUATECH™ STORM NOZZLES

25% more cleaning surface. This large 4 1/4" diameter nozzle places water closer to the pipe wall. Most efficient for grease, detergent and removal of large volumes of sand in sanitary sewers and drains. Cast aluminum body. For pipes 8" to 36" in diameter. Order all indicated parts in the appropriate column.



Part No.	Description	3/4" 40@2000	1" 65@2000	1" 80@2000
A131450	11/4" NPT Blank Storm Nozzle Body	1	1	1
A133790	11/4" to 3/4" NPT Pipe Reducer	1		
A133800	1 1/4" to 1" NPT Pipe Reducer		1	1
A131520	1/4" NPT #6 Rear Orifice	4		
A131526	1/4" NPT #8 Rear Orifice	4		
A131524	1/4" NPT #10 Rear Orifice		4	
A131523-SS	1/4" NPT #12 Rear Orifice			4
A131534	1/4" NPT #15 Rear Orifice		4	
A131530-SS	1/4" NPT #20 Front Orifice			4
A133350	1/8" NPT Front Plug			1
A131543	1/8" NPT #3 Front Orifice	Optional	Optional	Optional

ASSEMBLE YOURSELF O'BRIEN™ VORTEX GANG NOZZLES

For moving sand and debris through larger pipes. Cast aluminum body with 16 rear jets set at 15° and 30° angles and 1 forward jet. Order all indicated parts in the appropriate column.

Part No.	Description	3/4" 40@2000	1" 65@2000
J-1400	11/4" NPT Blank Gang Nozzle Body	1	1
A133790	11/4" to 3/4" NPT Pipe Reducer	1	
A133800	1 1/4" to 1" NPT Pipe Reducer		1
J-JET-116	3/8"-24 1/16" Orifice		17
J-JET-364	3/8"-24 3/64" Orifice	17	









DOUBLE STORM NOZZLE

The water from the leading set or orifices dislodges debris accumulations while the trailing set flushes the debris back to the manhole. Ideal for the rapid cleaning of medium and large pipes. Orifices are replaceable. An 1/8" pipe plug can be removed and substituted with an optional front orifice (p/n A131543) to create a penetrator nozzle.

Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
A130420	35°	16	Optional	65	2000	1"
A130422	35°	16	Optional	80	2000	1"
A130421	35°	16	Optional	100	2000	1-1/4"

SAND NOZZLES

Specially designed to lift and float sand that is otherwise difficult to move. For 4" to 18" pipes.



Part No.	Prop. Angle	Rear Jets	Fwd. Jets	GPM	PSI	NPT Size
016020SN	15°	6	2 @ 90°	60	2000	1"
016520SN	15°	6	2 @ 90°	65	2000	1"
018020SN	15°	6	2 @ 90°	80	2000	1"



TADPOLE NOZZLES

Our best all-around cleaning nozzle for 8" to 24" pipes. Highly effective at removing standing water and grease from pipe walls. The orifices are replaceable.

Part No.	Prop. Angle	Rear Jets	Front Jets	GPM	PSI	NPT Size
A136300	17º/24º	12	Optional	65	2000	1"
A136299	17º/24º	12	Optional	80	2000	1"





AQUATECH™ TORPEDO NOZZLES

This bottom cleaning nozzle features a towing eye, replaceable orifices and 360° rotating swivel to prevent hose from turning the nozzle and a smooth hardened surface to allow the nozzle to glide over sand and debris. 4" diameter, 24 lbs. approx. Imported.

Part No.	Prop. Angle	Rear Jets	Front Jets	GPM	PSI	NPT Size
A136185	35°	4	0	35	2000	3/4"
A136180	35°	4	0	65	2000	1"
A136187	35°	4	0	80	2000	1"
A136195	35°	4	0	100	2000	1-1/4"




ROTATING NOZZLES

ROTOR-JET POLISHER NOZZLES

Revolving nozzle creates a sheet of water with 360° of coverage maximized wall cleaning. Typically used as a finishing tool to remove debris which might have been missed because of the spaces between jets on a fixed orifice nozzle.

THE RESERVE OF THE PARTY OF THE	The Carlot of th			4	227	Company of the Compan
Part No.	Prop. Angle	Rear Jets	Side Jets	GPM	PSI	NPT Size
380530PO	45°	2	2 @ 90°	4.8	3000	3/8"
121840PO	30°	2	2 @ 90°	18	4000	1/2"
344020PO	30°	2	2 @ 90°	40	2000	3/4"





Custom drilled Rotor-Jet nozzles are available to meet your specifications. All Rotor-Jet can accommodate spray angles between 45° to 90°. NOTE: 1/2" NPT Rotor-Jets can accommodate a higher thrusting angle of 30°.

Pattern: 2 jets (one angle) or 4 jets (two angles) within available range.

Made of Heat Treated 416 stainless steel. See caution note on page 1.

A NOTE ABOUT ALL OF OUR ROTATING NOZZLES: In order to extend the life of these nozzles, we recommend submerging them in lubricating oil after each use.

11 06 202





SPIN CLEAN NOZZLES

This stainless steel rotating nozzle scours the pipe wall loosening hard debris. Ideal for pipes with limestone and other mineral deposits. Also effective for removing grease build-up.

Centering skids are recommended to achieve the best cleaning action. Imported.



ď		Section 1975 Business	CASTANCE CO.	CARLON TO BE A STORY		75.200 (EE A)	NEWS TREETED IN
	Part No.	Prop. Angle	Rear Jets	Side Jets	GPM	PSI	NPT Size
Company of the last	A136070	30°	6	4 @ 900	35	2000	3/4"
100	A136065	30°	6	4 @ 900	65	2000	1"
	A136060	30°	6	4 @ 90º	80	2000	1"
i de	A136062	30°	6	4 @ 90°	100	2000	1 1/4"

CONICAL DRILL NOZZLES

Designed to cut, drill and penetrate difficult obstructions in 3" and larger pipes. Centering skids are recommended. 60° carbide flutes can be re-sharpened.



Part No.	Prop. Angle	Rear Jets	Rotor Jets	GPM	PSI	NPT Size
A136345	25°	6	6	35	2000	3/4"
A136135	25°	6	8	65	2000	1"

PROPELLER NOZZLES

Designed to cut through solid blockages and roots. Centering skids are recommended. Imported.



Part No.	Prop. Angle	Rear Jets	Rotor Jets	GPM	PSI	NPT Size
A136105	25°	6*	5	35	2000	3/4"
A136100	25°	6*	5	60	2000	1"
A136102	25°	6*	5	80	2000	1"

A NOTE ABOUT ALL OF OUR ROTATING NOZZLES: In order to extend the life of these nozzles, we recommend submerging them in lubricating oil after each use.





ROTATING CHAIN NOZZLES

Chains rotate at a high speed removing hard deposits, such as slag, calcium and limestone. Also good for paint, epoxy and other accidental spills. Will open blockages caused by grease, sand and roots. Square profile chain made of high quality steel. Centering skids are recommended. Orifices are replaceable. Imported.

Part No.	Prop. Angle		Rotor Jets	GPM	PSI	NPT Size
A136240	20°	4	4	35	2000	3/4"
A136245	20°	6	6	65	2000	1"
A136244	200	6	6	80	2000	1"





WARNING: In order to avoid possible property damage and personal injuries when handling these tools, we recommend that the nozzle be exposed to gradual system pressure only after it has been set and secured inside the pipe, away from the operator. Hi-Vac Corporation is not responsible for situations resulting from the improper use of this tool and for different operation from that it has been designed and intended for.

REPLACEMENT CHAIN ROTATING CHAIN NOZZLES

Three required per nozzle (except for bulk replacement chain).

A STATE OF THE PARTY OF THE PAR	PRODUCE AND ADDRESS OF THE PROPERTY.	AND THE RESIDENCE OF THE PARTY			
	For 1/2" & 3/4" Nozzles		For 1" & 1-1/4" Nozzles		
Length	Part Number	Approx	Part Number	Approx	
6" Long (150mm)	A136241 * 4" to 6"		N/A		
12" Long (300mm)	A136251	8" to 12"			
16" Long (400mm)				14" to 18"	
20" Long (500mm)	N/A		TBA	18" to 22"	
36" Long (900mm)	A136241-6	Bulk Replacement Chain	A136242-6	Bulk Replacement Chain	

^{*}standard length supplied with nozzle.

A NOTE ABOUT ALL OF OUR ROTATING NOZZLES: In order to extend the life of these nozzles, we recommend submerging them in lubricating oil after each use.









LATERAL LINE ROOT CUTTER KITS

Powered by the jetter's water pressure, these fierce root cutters spin at extremely high torque. Kits include tool box and all necessary hardware. 5/8" output shaft.

A CONTRACTOR OF THE PARTY OF TH	CARRIED COST CONTRACT	and the same of	The state of the s	
Part No.	GPM	PSI	NPT Size	Saws & Skids Included
J-1469-34	35-50	900-1400	3/4"	4", 6", 8", 10" (concave saws)
J-1469	50-80	900-1400	1"	4", 6", 8", 10" (concave saws)





MAINLINE ROOT CUTTER KITS

Powered by the jetter's water pressure, these fierce root cutters spin at extremely high torque. Kits include tool box and all necessary hardware. 1" output shaft.

Part No.	GPM	PSI	NPT Size	Saws & Skids Included
J-1603-P	35-80	900-1500	1"	4", 6", 8", 10" (concave saws)

REPLACEMENT AND OPTIONAL ROOT CUTTER SKIDS

Root Cutter Attachments			
X-	Skids for Lateral Line RC	Skids for Mainline RC	Optional Skids w/ Wheels
6" pipe	J-1469-6	J-1603-6S	
8" pipe	J-1469-8	J-1603-8S	J-1603-8SW
10" pipe	J-1469-10	J-1603-10S	J-1603-10SW
12" pipe	J-1569-12	J-1603-12S	J-1603-12SW
15"pipe		J-1603-15S	J-1603-15SW





REPLACEMENT AND OPTIONAL ROOT CUTTER BLADES


	0	0	(2)	5
	Flat Saws	Concave Saws	Tapered Saws	Cutter Blades
3" pipe	M-1003			
4" pipe	M-1004	M-2004	M-3004	
6" pipe	M-1006	M-2006	M-3006	A131010
8" pipe	M-1008	M-2008	M-3008	A131020
10" pipe	M-1010	M-2010	M-3010	A131030
12" pipe	M-1012	M-2012	M-3012	A131040
15" pipe	M-1015	M-2015	M-3015	A131050
18" pipe	M-1018	M-2018	M-3018	







J-1700-P




Part No.	Description
J-1469-BH	Root Cutter saw chuck for Lateral Line (5/8" output shaft) root cutters
J-1700-P	Root Cutter saw chuck for Mainline (1" outout shaft) root cutters
J-7000	Cutter Blade chuck for obsolete O'Brien™ (1" output shaft) root cutters
A131080	Cutter Blade chuck for absolute Aquatech™ (1" output shaft) root cutters

NOTE: Either of the above cutter blade chucks will fit the newer mailine root cutter if user wishes to use the cutter blades.







Centers nozzle in the pipe. Cuts nozzle wear by 50%. A must for all rotating nozzles. Maximizes cleaning efficiency for any nozzle that sprays in a 360° (radial) pattern. Female NPT on the inlet end for the hose and male NPT on the outlet end for the nozzle.

A STATE OF THE PARTY OF THE PAR	STATE OF THE STATE	THE REPORT OF THE PARTY OF THE	
Part No.	1/2" NPT	3/4" NPT	1" NPT
4" ID Pipe	J-4012-04	J-4034-04	J-4001-04
6" ID Pipe	J-4012-06	J-4034-06	J-4001-06
8" ID Pipe	J-4012-08	J-4034-08	J-4001-08
10" ID Pipe	J-4012-10	J-4034-10	J-4001-10
12" ID Pipe	J-4012-12	J-4034-12	J-4001-12
15" ID Pipe			J-4001-15

NOZZLE EXTENSIONS

Prevents the sewer hose from reversing direction in larger pipes. Also prevents nozzle from entering a lateral pipe. Helps reduce wear on sewer hose.



Part No.	Length	NPT Size
J-40-3	12"	1/2"
A130004	12"	3/4"
A130005	10"	1"
A130001	12"	1"
A130002	12"	1-1/4"



American made with investment cast steel process.

ì	A STATE OF THE STA		
Š	Part No.	Input	Output
1	A130729	3/4" FNPT	3/4" FNPT
1223.884	J-2405-2	1" FNPT	1" FNPT
THE PARTY	A130727-1	1-1/4" FNPT	1-1/4" FNPT





TRAP HOSE

For cleaning residential and industrial "S" traps and other small diameter lines.

600	Part No.	Hose Size	Hose Length	NPT Hose Ends	Hose PSI
1000	15030-025	1/8"	25'	1/8"M x 1/8"M	3000

THE STATE OF THE S

TRAP HOSE KITS

Trap hose with nozzle.

Part No.	Hose Size	Hose Length	NPT Hose Ends	Hose PSI	Nozzle	NPT Adapter
OBJ-1723K	1/8"	25'	1/8"M X 1/8"M	4000	1/8" 4gpm	1/8"F to 1/4"F
OBJ-1722K	3/16"	75'	1/4"M X 1/8"M	4000	1/8" 4gpm	3/8"F to 1/4"F
A136260	1/4"	65'	1/4"FS X 1/8"M	5800	1/8" 3-20gpm	None

COBRA SEWER CLEANING HOSES


Constructed from materials selected to provide rugged and reliable service under even the most severe and demanding conditions found in high pressure sewer cleaning. These sewer cleaning hoses are constructed with a polyolefin tube which provides maximum resistance to the hydrolysis commonly associated with other thermoplastic tube materials. Reinforcement with high tensile polyester fiber contributes to an exceptionally low volumetric expansion rate and eliminates loss of strength from moisture absorption. A polyether-urethane cover provides exceptional cut, abrasion and fungus resistance. All components are bonded together to maximize fitting retention and wear resistance, and to provide smaller minimum bend radii.

Size	3/8"	1/2"	3/4"			1"	
Ends	3/8" MNPT	1/2" MNPT	3/4" MNPT		1"	1" MNPT	
Press.	4000 PSI	4000 PSI	2500 PSI 3000 PSI		2500 PSI	3000 PSI	
Color	Green	Green	Orange	Blue	Orange	Blue	
100'	available	J-1942-100-COBRA	A175150-10-COBRA	available	available	available	
150'	20032-150-COBRA	J-1942-150-COBRA	A175150-11-COBRA	available	available	available	
200'	20032-200-COBRA	J-1942-200-COBRA	available	available	A175213-COBRA	available	
250'	available	available	available available		available	available	
300'	available	J-1942-300-COBRA	available available		available	available	
400'	available	J-1942-400-COBRA	A175150-21-COBRA	A175166-3000-COBRA	A175231-COBRA	A175233-3000-COBR	
500'	available	J-1942-500-COBRA	A175150-27-COBRA	A175150-22-COBRA	A175241-COBRA	A175241-3000-COBR	
600'	available	J-1942-600-COBRA	A175150-23-COBRA	A175167-3000-COBR	A175252-COBRA	A175252-3000-COBR	
700'		J-1942-700-COBRA	A17150-24-COBRA A175168-3000-COBR		A175161-COBRA	A175261-3000-COBR	
750'		available	A175150-26-COBRA available		available	available	
800'		J-1942-800-COBRA	A175150-25-COBRA	A175169-3000-COBR	A175271-COBRA	A175271-3000-COBR	
900'		available	available	available	available	available	
1000'		available	J-1940-1000P	A175171-3000-COBR	A175269-COBRA	A175269-3000-COBR	
1100'				available	available	available available	
1200'			available		available	available	












Part No.	Size
A255078-1/2-D	1/2"
A25507-3/4-D	3/4"
A255078-1-D	1"





COBRA PUSHERS





MERCHANIS CO.	Section Control of the Control of th	Marie Control of the Control	
BEST STORY		SPECIAL CONTRACT	
0000			
CORR			

Pai	rt No.	Description		
A255078		Hydraulic Swage Tool		
A25	5078-M	Manual Swage Tool		

PN for Male	PN for Female	Size
A255078-1/2-P	ТВА	1/2" MNPT
A25507-3/4-P	ТВА	3/4" MNPT
A255078-1-P	A255078-1-FP	1" MNPT

COBRA SEWER HOSE SWAGE FITTINGS

These swage fittings are specifically designed for the sewer hose we sell. Note: Manufacturer's swaging equipment required to install these ends. Use of other fittings and equipment is at users own risk. Due to the higher pressures involved with 3/8" and smaller hoses, the manufacturer does not supply replacement fittings for them.

Hose Size	1/2"	3/4"	1"	
	17 2	O/ 1		Dogwined Teeling
Working PSI	3000 & 4000	2500 & 3000	2500 & 3000	Required Tooling
Male End	J-1942-1-COBRA	A170040-COBRA	A170020-COBRA	Die set & male pusher
Female End	J-1942-2-COBRA	J-1941-4-COBRA	J-1941-4-COBRA	Die set & female pusher
Mender	J-1942-3-COBRA	A170030-COBRA	A170030-COBRA	Two die sets



1.06.202





LEADER HOSES

Most of the wear on a sewer cleaning hose occurs on the first several feet working through the sewer. By adding a leader hose one can extend the life of the main roll of hose. Female fitting on hose end to male fitting on nozzle end.

CAN DESCRIPTION OF THE PARTY OF	A STATE OF THE STA	West of the second		The Political State of the Political Control o	
Part No.	NPT Size	Length	Max Working	Cover Material	Stocking Status
J-1909	3/8"	20'	4000 PSI	Thermoplastic	Normally Stocked
J-1910	1/2"	20'	4000 PSI	Thermoplastic	Normally Stocked
J-1931	3/4"	10'	3000 PSI	Thermoplastic	Special Order
A176105	3/4"	10'	2500 PSI	Rubber	Special Order
J-1905	3/4"	20'	2500 PSI	Rubber	Normally Stocked
A176106	3/4"	20'	3000 PSI	Rubber	Normally Stocked
A249253	3/4"	25'	3000 PSI	Rubber	Special Order
J-1933	1"	10'	2000 PSI	Thermoplastic	Special Order
A176100 REV B	1"	10'	3000 PSI	Rubber	Normally Stocked
J-1924	1"	15'	3000 PSI	Thermoplastic	Normally Stocked
A176110	1"	20'	2000 PSI	Rubber	Normally Stocked
A176115	1"	25'	2000 PSI	Rubber	Special Order
J-1934	1"	25'	2500 PSI	Thermoplastic	Normally Stocked
A176101	1-1/4"	10'	2000 PSI	Thermo	Special Order

"LIVE" SWIVELS

Allows attachments to swivel freely without twisting the hose. Male pipe to female pipe.

Hose Size	1/2" Hose	3/4" Hose	1" Hose	9
Part Number	A130847	A130848	A130849	

SWIVEL UNIONS

Female pipe to female pipe swivel unions for joining two sections of hoses together.

Hose Size	3/16" Hose	1/4" Hose	3/8" Hose	1/2" Hose	3/4" Hose	1" Hose
Part Number	9255X2X2	9255X4X4	9255X6X6	A381980	A338105	A130690

STEP DOWN SWIVEL UNIONS

For joining a smaller size sewer hose to a larger size. For attaching line kits, pressure wands, etc. Note: Be careful not to exceed the pressure rating of your unnit.

Hose Sizes	3/8" to 1/4"	1/2" to 3/8"	3/4" to 1/2"	1" to 3/4"
Part Number	9255X6X4	9255X8X6	9255X8X12	A249058










FOOT CONTROL

For auxiliary hose reels and lateral line kits. Note: "Dry Shut" foot controls will dead head the inlet when pedal is not depressed.

Part No.	Style	Inlet Port NPT	Outlet Port NPT	Dump Port NPT	Max GPM	Max PSI
10000407	Dry Shut	3/8" F	1/4" F	none	12	3000



REELS

Part No.	Hose Size	Adapter Req.*	Reel Capacity	Spool Width	Max PSI
	1/4"	A133640	200'	C"	2000
A130560	3/8"	A133650	150'	6"	3000
	1/2"	none	100'		
	1/4"	A133640	400'	42"	2000
30018	3/8"	A133650	300'	12"	3000
	1/2"	none	200'		

	Part No.	Description
CAMPACING	A130555	Cart for 12" Wide Hose Reel
900	A130555-18	Cart for 18" Wide Hose Reel



CART FOR AUXILIARY HOSE REEL



FLEXIBLE HOSE GUIDE (TIGER TAIL)

Protects the sewer cleaning hose from chafing against the edge of the pipe inside a manhole. Includes a rope for lowering and securing the guide thus eliminating the need to enter the manhole.

With Rope	I.D.	Length	Rope Length
J-2203	3"	36"	24'

11.06.202







TOP MANHOLE ROLLER

Used when manholes are not in line with the reel. Protects hose from scuffing and allows hose to glide over manhole edge.

Part No.	Width	Length
J-2401	12"	38"



ALUMINUM MANHOLE SAFETY COVER

The wire grid safely covers the manhole but still allows for good visibility below. Bolts on the rim allow for adjustment to keep the cover centered in the opening.

Part No.	Width
J-2026	20" to 26" Manholes
J-2634	26" to 34" Manholes



HYDRANT WRENCH

Part No.	Description
A220330	Hydrant Wrench



HINGED TOP MANHOLE ROLLER

The legs of this manhole roller are hinged which allows them to spread out to make room for boom hose to enter manhole.

Part No.	Width	Length
J-2402	13"	41"

2.5" NST HYDRANT FILL HOSE

	Part No.	Description	
1000	A176150	2-1/2" ID x 25'	
2000	A176154	2-1/2" ID x 50'	





MANHOLE HOOK

Part No.	Description
A221800	29" w/ Perpendicular T-Handle



MANHOLE LIFTER & PICK

Part No.	Description
J-4000	36" L Manhole Pick & Hook Combo

11 06 20



