



7000 SERIES

REEL STAYING POWER



190° Rotating Hose Reel



Non-CDL Chassis Option



700-Gallon Onboard Water Capacity



Full Length Tool Trays

- Tier 4 US-made no-DEF diesel powerplant
- Water pumps offering 18 to 40 GPM & 2,000 to 4,000 PSI
- 700-gallon fresh-water capacity
- 190° rotating hose reel
- Up to 600' of jetting hose
- Weather-resistant mechanical enclosure
- Fits on Class 5 or greater chassis

7000 SERIES STANDARD SPECIFICATIONS



WATER SYSTEM

- Triplex run-dry water pump, choice of 18 GPM and 4,000 PSI, 30 GPM and 3,000 PSI, or 40 GPM and 2,000 PSI
- Pump is belt-driven and disengagable from powerplant
- Dual basket-style intake strainers
- Water pump drain and cold-weather blow-out package
- Cold weather recirculation package

WATER TANKS

- Dual centerline-mounted tanks, 700 gallons total fresh-water capacity
- 3/8" thick polyethylene UV stabilized, with 10-year warranty
- Single fill point with anti-siphon device & 2 1/2" coupling
- Rear water level sight gauge
- Optional 25' x 2 1/2" hydrant fill hose
- Optional fill hose basket

HOSE REEL SYSTEM

- Up to 600' of 1/2" or 3/4" hose available
- Attached to rear unit frame
- 190° street to curb rotation
- Hydraulically powered forward/reverse reel
- Variable speed control
- Optional auto level wind and level wind with counter
- Standard 20' leader hose
- Optional split reel, 3/4" x 500' and 1/2" X 300'

POWERPLANT

- 74 HP Tier 4 diesel engine
- 16.5 quart oil capacity
- No DEF required
- 16-gallon fuel tank
- Low oil pressure, high temperature auto-shutdown systems

CHASSIS

- Hi-Vac or customer-supplied Class 5 or greater chassis
- Contact factory for chassis spec approval
- Class 5 or 6 configurations under CDL weight limit

ENCLOSURE

- Heavy-duty steel construction
- Protects engine and pump
- Keyed dual access doors

LIGHTING

- DOT certified LED lighting and wiring compliant to FMVSS 108

CONTROLS

- Controls located within a NEMA 4 weatherproof enclosure
- Enclosure mounted on curb side of unit, rotates with hose reel
- Tachometer with hour meter, water pump, hydraulic, oil pressure and temperature gauges, volt-meter, electronic engine throttle, engine protection bypass switch, dual 12V accessory plugs, hose reel speed control, low water warning light
- Standard tethered remote control
- Optional wireless remote control

STORAGE

- Standard expanded metal basket
- Standard full length tool trays
- 3 sizes of optional toolboxes

OPTIONS & ACCESSORIES

- Enclosure and work light package
- Digital footage counter
- Low water shutdown
- Lateral cleaning kits
- Washdown gun with hose
- Nozzle extensions
- Nozzle guards for 4" to 12" pipes
- Custom paint
- Custom graphics